

MATERIAL SAFETY DATA SHEET

Page 1 of 5

Sculpt Nouveau

Metal Oil - Natural and Darkened

DATE REVISED: 05.03.06 REVISION MSDS No. 1

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Sculpt Nouveau Meta Oil
Manufactured By: Sculpt Nouveau
PO Box 460459
Escondido, CA 92049
800728-5787 Fax 760-741-1074

**24 HOUR TRANSPORTATION EMERGENCY NUMBER: CHEMTREC 800-424-9300 U.S. & CANADA
202-483-7616 INTERNATIONAL**

2

2. COMPOSITION / INFORMATION ON INGREDIENTS

DESCRIPTION	CAS NUMBER	WEIGHT PERCENT	EXPOSURE LIMITS
Mineral Spirits	8052-41-3	<57	500 ppm ^(a)
Modified Oil	Mixture	<33	NE ^(b)
Linseed Oil	Mixture	<11	NE ^(b)

(a) OSHA PEL

(b) None Established

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Opaque light brown liquid, solvent odor. Skin and eye irritation – direct contact.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Frequent or prolonged contact may irritate and cause dermatitis. Low order of toxicity.

INGESTION: Irritation of mouth and throat. Aspiration into lungs may cause mild to severe pulmonary injury.

INHALATION: High vapor concentrations may be irritating to the respiratory tract. Other possible symptoms include headaches, dizziness and drowsiness.

CHRONIC: Not established.

Sculpt Nouveau

Metal Oil - Natural and Darkened

DATE REVISED: 05.03.01 REVISION MSDS No. 1

4. FIRST AID MEASURES

EYE CONTACT: Flush thoroughly with water for 15 minutes. Consult physician.

SKIN CONTACT: Remove contaminated clothing to prevent further contact. Wash affected areas of skin with soap and water.

INGESTION: **DO NOT** induce vomiting. Contact physician immediately.

INHALATION: Remove to fresh air. Provide artificial respiration, if necessary.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: 111°F/125°F

METHOD USED: TCC/TOC

FLAMMABLE LIMITS:

LFL: 1.0 UFL: 6.0

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foam or other extinguisher rated for Class B fires.

FIRE & EXPLOSION HAZARDS: None Known.

SPECIAL FIRE FIGHTING PROCEDURES: Do not flood with water. Use water only as a fine mist if more suitable extinguishing agents are unavailable.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Review current local, state and federal laws, codes, statutes, and regulations to determine appropriate agencies to be notified, and the conditions under which they are to be notified. Eliminate ignition sources. Ventilate area. For massive spills, evacuate area of persons not wearing protective equipment and clothing. Recover as much free liquid as possible. Use absorbent to pick up residue. Avoid discharging the liquid directly into a sewer or surface waters. CERCLA Reportable Quantity is 100 lbs. for an ignitable waste.

WASTE DISPOSAL METHOD: Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Waste concentrate is assigned the EPA Hazardous Waste Number D001 (Ignitability). The material can be disposed of through a licensed waste disposal company.

Sculpt Nouveau**Metal Oil - Natural and Darkened DATE REVISED: 05.03.01 REVISION MSDS No. 1**

7. **HANDLING AND STORAGE:** Store in clean, fire-resistant storage area with good ventilation and not subject to high temperatures. Prohibit smoking in the area and exclude sources of spark or open flame. Store liquid in closed containers.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

NOTE: The product itself does not produce hazardous fumes or vapors. Consequently, no ventilation or respiratory protection is required under normal operating conditions. However, if the product is sprayed, then appropriate ventilation and respiratory protection is recommended.

RESPIRATORY PROTECTION (type): Air-supplied or self-contained breathing apparatus if sprayed.

PROTECTIVE GLOVES (type): Rubber or polyvinyl.

LOCAL EXHAUST VENTILATION (rate): As required to control exposure below TLV.

EYE PROTECTION: (type): Safety glasses, goggles, or face-shield.

MECHANICAL VENTILATION (rate): As needed.

OTHER PROTECTIVE EQUIPMENT: As needed to minimize exposure or contamination.

SPECIAL VENTILATION: Equipment for collection and containment of mist if spray application is used.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >315°F

SPECIFIC GRAVITY: 0.825

VAPOR PRESSURE: No Data.

VOLATILE BY VOLUME: 60%

VAPOR DENSITY: (Air = 1) >1

EVAPORATION RATE: (Ethyl Ether = 1) <1

SOLUBILITY IN WATER: Immiscible

pH (100%) : N/A

APPEARANCE & ODOR: Brown liquid with kerosene like odor.

pH (10%) : N/A

10. STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid high temperatures and ignition sources.

INCOMPATIBILITY (materials to avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Products of combustion include oxides of carbon and sulfur.

HAZARDOUS POLYMERIZATION: Will not occur.

Sculpt Nouveau

Metal Oil - Natural and Darkened DATE REVISED: 05.03.01 REVISION MSDS No. 1

11. TOXICOLOGICAL INFORMATION

Refer to Section 3 for available information on potential health effects.

CALIFORNIA PROPOSITION-65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

This product contains [or may contain] trace amounts of organic compounds that have been listed pursuant to Proposition 65, California Health & Safety Code Section 25249.8. Employers may have an obligation to warn their employees and other on their premises of potential exposure to Proposition 65 listed substances. If this product is sold or used in or incorporated into a product sold in California, California law may require that the manufacturer, distributor and retailer of the product provide a warning pursuant to Proposition 65, California Health & Safety Code Section 25249.6. Failure to provide required warnings may result in legal liability. This product may not be discharged onto land or into any source of drinking water in California.

12. ECOLOGICAL INFORMATION

Data not available.

13. DISPOSAL CONSIDERATIONS

Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be dealt with by a licensed facility or waste hauler.

14. TRANSPORT INFORMATION

D.O.T. HAZARDOUS MATERIALS DESCRIPTION AND PROPER SHIPPING NAME:

Flammable Liquid N.O.S. /3/UN1993/P.G. III (Naphtha, Petroleum)
Exceptions may apply: 49CFR 173.150

15. REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION RULE 29 CFR 1910.1200: Combustible (Mineral Spirits).

TSCA (TOXIC SUBSTANCES CONTROL ACT): The materials in this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Response compensation and Liability Act, 40 CFR 117, 302: Not applicable.

SARA TITLE III (Superfund Amendments and Authorization Act): Section 311/312 – fire hazard.

Sculpt Nouveau**Metal Oil - Natural and Darkened DATE REVISED: 05.03.0 REVISION MSDS No. 1****15. REGULATORY INFORMATION – (Continued)**

CALIFORNIA PROPOSITION-65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

This product contains [or may contain] trace amounts of organic compounds that have been listed pursuant to Proposition 65, California Health & Safety Code Section 25249.8. Employers may have an obligation to warn their employees and other on their premises of potential exposure to Proposition 65 listed substances. If this product is sold or used in or incorporated into a product sold in California, California law may require that the manufacturer, distributor and retailer of the product provide a warning pursuant to Proposition 65, California Health & Safety Code Section 25249.6. Failure to provide required warning may result in legal liability. This product may not be discharged onto land or into any source of drinking water in California.

16. OTHER INFORMATION

NATIONAL FIRE PROTECTION ASSOCIATION CODES (NFPA):

HEALTH: 1 FLAMMABILITY: 2
 REACTIVITY: 0

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS):

HEALTH: 1 FLAMMABILITY: 2
 REACTIVITY: 0 PERSONAL PROTECTION: C

The data here is for hazard communication to our employees, our customers and their employees, and authorized regulatory agencies. For the intended purpose, this MSDS (Material Safety data Sheet) may be duplicated or the data transcribed to an alternative form.

NOTE: The information contained herein is provided in good faith and is believe to be correct as of the date hereof. However, Sculpt Nouveau makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular period. Accordingly, Sculpt Nouveau. will not be responsible for damages of any kind resulting from the use of or reliance upon such information. NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER TO WHICH THE INFORMATION REFERS. The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.